



ACROSS INTERNATIONAL

Model	FO19440
Electrical Requirements	208-240VAC 50/60Hz single phase, 4000 watts
Chamber Dimensions	27 x 25 x 35.5" (WxDxH)
Unit Dimensions	33.5 x 34 x 52.25" (WxDxH)
Shipping Dimensions	39 x 41 x 61" (WxDxH)
Temperature range	Ambient temperature to 250°C
Heating Elements	In the back of the oven
Timer Range	1 to 9999 minutes
Racks Included	2 (additional racks available at extra cost)
Maximum Rack Capacity	16 (height between each rack is 2 inches)
Moisture Escape Port	1.5" diameter x 2, adjustable (on top of the oven)
Access Port	2" diameter x 1, with covers
Shipping Weight	562 Lb
Certification	ETL tested to UL and CSA standards (optional), CE
Warranty	One year

Model	FO22
Electrical requirements	220V 50/60Hz 1-Phase 31.8A 7000 watts
Chamber dimensions	31 x 31 x 39" (WxDxH)
Unit dimensions	37.5 x 40 x 57" (WxDxH)
Shipping dimensions	45 x 45 x 64" (WxDxH)
Temperature range	Ambient temperature to 250°C
Timer range	1 to 9999 minutes
Racks included	2 (additional racks available at extra cost)
Maximum rack capacity	17 (height between each rack is 2 inches)
Moisture escape port	2" diameter x 2, adjustable (on top of the oven)
Access port	2" diameter x 1, with covers
Unit Weight	510 Lbs
Shipping weight	700 Lbs
Certification	ETL tested to UL and CSA standards (optional), CE
Warranty	One year