



ACROSS INTERNATIONAL

EasyVac Pumps Series Specification

Model	EV7	EV9
Electrical requirements	110V/220V 50/60Hz switchable, 1-Phase, 1/2 HP	110V/220V 50/60Hz switchable, 1-phase, 1 HP
Output Power	370 W	750 W
Pumping rate	7 cfm (110V 60Hz) 6 cfm (220V 50/60Hz)	9 cfm (110V 60Hz) 8 cfm (220V 50/60Hz)
Vacuum level	150 micron/millitorr	15 micron/millitorr
Vacuum connection	3/8" hose barb	KF25/NW25 flange
Exhaust filter connection	KF25/NW25 flange	KF25/NW25 flange
Oil volume	415 mL / 0.44 quart	560 mL / 0.6 quart
Motor rate	1720 rpm	
Working temperature	-5 to 60°C	
Unit weight	22 lbs.	37 lbs.
Shipping weight	23 lbs.	41 lbs.
Unit dimensions (LxWxH)	13 x 5 x 10"	16.5 x 6 x 16"
Shipping dimensions (LxWxH)	18 x 7 x 11.5"	20 x 9 x 13"
Recommended Oil	Ultra grade 19	
Compliance	UL/CSA, CE	
Warranty	One year	