



FISCHER TECHNICAL COMPANY

High Vacuum Pumps



Item: LAV-5

These 5 CFM (142 l/m) rotary style, 2 stage direct drive pumps are ideal for use in virtually all high vacuum applications. Our pumps are tested to 15 microns Hg but are suitable for all applications requiring a vacuum under 500 microns Hg. The pumps use High Vacuum Pump Oil (one quart included) and are designed to run on a closed and dry system. Regular oil changes and proper maintenance will ensure these pumps will last for years in your laboratory.

Phone 630-980-9881 Email: sales@fischertech.com 840 W Lake St STE 404 Roselle, IL 60172

Get it from your authorized distributor: www.labequip.com



ask@labequip.com



FISCHER TECHNICAL COMPANY

LAV-5 Specifications



High Vacuum Pump Specifications	
Free Air Displacement	142 l/m or 5 CFM
Factory Micron Rating	15 microns
Stages	2
Intake Fitting	3/8th inch Intake Hose Barb
Oil Capacity	23 oz (680cc)
Vacuum Pump Oil Refill	OIL-012 (12 Quarts) and OIL-PK (2 Quarts)
Motor Size	1/2 HP
Voltage	US 110V 60Hz
Approvals	UL Recognized
Shipping Weight	32 LBS
Shipping Dimensions	11" H x 14" L x 5 1/4" W (27.5cm x 35cm x 12.5cm)
Operating Temperature	30° F to 170° F
Pump Speed	1725 RPM
Manufactured In	USA

Phone 630-980-9881 Email: sales@fischertech.com 840 W Lake St STE 404 Roselle, IL 60172

Get it from your authorized distributor: www.labequip.com



ask@labequip.com