

PM R Moisture Analyzers

Cutting-edge solutions and a high quality measurement in drying process and moisture content analysis



Communication interfaces



Large LCD screen with text information line

Functions

- 

Moisture content analysis
- 

Drying modes
- 

GLP procedures
- 

Replaceable unit
- 

Multilingual menu
- 

Dry mass determination

Features

Measurement Precision Along with High Performance and Productivity

Due to combination of simplicity of operation, great measurement accuracy and high performance, the PM R moisture analysers can be used for vast range of moisture content determination processes.

Mass Measurement Accuracy and Drying Temperature Optimisation

Smart control of heating modules operation guarantees optimum drying temperature, plus fast and precise measurement. At your disposal there are numerous drying profiles ensuring various methods of obtaining the pre-set temperature.

Perfect Readability and Clear Information Layout

Large, easy-to-read LCD display offers not only a clear presentation of the weighing result, but also enables displaying messages related to the drying process as well as pictograms of active functions and working modes.

Quick Access to Selected Functions

Quick access keys located on the operation panel enable you to run a given function with just one click. You can assign some of the keys with a selected function.

Databases as Drying Processes Support

Possibility to record sample-related information and drying parameters in the database improves managing of measurement processes and makes comfort of operation more advanced.

Technical Specifications

	PM 50/1.R	PM 50.R
Maximum capacity [Max]	50 g	50 g
Readability [d]	0.1 mg	1 mg
Tare range	−50 g	−50 g
Maximum sample weight	50 g	50 g
Drying temperature range	max. 160°C, max. 250°C (option)*	max. 160°C, max. 250°C (option)*
Moisture content readability	0.0001%	0.001%
Moisture content repeatability	0.05% (ca. 2 g sample), 0.01% (ca. 10 g sample)	0.05% (ca. 2 g sample) 0.01% (ca. 10 g sample)
Adjustment	external	external
Display	LCD (backlit)	LCD (backlit)
Keypad	14 keys	14 keys
Heating module	IR emitter halogen lamp (option)** metal heater (option)**	IR emitter halogen lamp (option)** metal heater (option)**
Databases	6	6
Drying profiles	standard, fast, step, mild	standard, fast, step, mild
Finish mode	manual, automatic, time-defined, user-defined	manual, automatic, time-defined, user-defined
Additional functions	sample traceability	sample traceability
USB-A	1	1
USB-B	1	1
RS 232	1	1
Wireless connection (option)***	802.11 b/g/n	802.11 b/g/n
Power supply	230 V	230 V
Power consumption	4 W (during weighing) and max 450 W (during drying)	4 W (during weighing) and max 450 W (during drying)
Heating module power	450 W	450 W
Operating temperature	+10 ÷ +40 °C	+10 ÷ +40 °C
Atmospheric humidity****	40 ÷ 80%	40 ÷ 80%
Transport and storage temperature	−20 ÷ +50 °C	−20 ÷ +50 °C
Maximum sample height	h= 20 mm	h= 20 mm
Weighing pan dimensions	ø 90 mm, h= 8 mm	ø 90 mm, h= 8 mm
Weighing device dimensions	333 × 206 × 190 mm	333 × 206 × 190 mm
Net weight	4.8 kg	4.8 kg
Gross weight	6.3 kg	6.3 kg
Packaging dimensions	470 × 380 × 336 mm	470 × 380 × 336 mm



* optional design with halogen lamp – max temperature 250° C
** optional design with preferable heating module: halogen lamp – WH version, metal heater – NS version
*** option: moisture analyzer with a Wireless Connection module
**** non-condensing conditions

PM 210.R

Maximum capacity [Max]	210 g
Readability [d]	1 mg
Tare range	−210 g
Maximum sample weight	210 g
Drying temperature range	max. 160°C, max. 250°C (option)*
Moisture content readability	0.001%
Moisture content repeatability	0.05% (ca. 2 g sample), 0.01% (ca. 10 g sample)
Adjustment	external
Display	LCD (backlit)
Keypad	14 keys
Heating module	IR emitter halogen lamp (option)** metal heater (option)**
Databases	6
Drying profiles	standard, fast, step, mild
Finish mode	manual, automatic, time-defined, user-defined
Additional functions	sample traceability
USB-A	1
USB-B	1
RS 232	1
Wireless connection (option)***	802.11 b/g/n
Power supply	230 V
Power consumption	4 W (during weighing) and max 450 W (during drying)
Heating module power	450 W
Operating temperature	+10 ÷ +40 °C
Atmospheric humidity****	40 ÷ 80%
Transport and storage temperature	−20 ÷ +50 °C
Maximum sample height	h= 20 mm
Weighing pan dimensions	ø 90 mm, h= 8 mm
Weighing device dimensions	333 × 206 × 190 mm
Net weight	4.8 kg
Gross weight	6.3 kg
Packaging dimensions	470 × 380 × 336 mm

* optional design with halogen lamp – max temperature 250° C
** optional design with preferable heating module: halogen lamp – WH version, metal heater – NS version
*** option: moisture analyzer with a Wireless Connection module
**** non-condensing conditions

Dimensions



Accessories

Weighing Tables

- antivibration tables for laboratory balances

Weighing Tables

- antivibration tables for laboratory balances

Special Purpose Weighing

- water vapour permeability determination set

Ambient Conditions

GT105K-12/Z control thermometer

Peripheral Devices

- Epson dot matrix printer
- barcode scanners

Consumables

- disposable pans

Cables, Converters

- P0108: RS 232 cable (balance-computer)
- P0151: RS 232 cable (balance - Epson printer)

Dedicated Software

Alibi Reader

- readout of Alibi memory stored data
- export of Alibi memory stored data
- data filtering and reports generating
- saving ALIBI database to CSV file

LabView Driver

- operation of RADWAG balances in LabView environment

E2R Moisture Analyzer

- drying programs synchronization
- online preview of the drying process
- drying processes record
- reporting of single and group drying operations