

Magnetic Hotplate Stirrers

HP380-Pro LCD Digital Hotplate

MS6-Pro LCD Digital Magnetic Stirrer

MS-H380-Pro LCD Digital Magnetic Hotplate Stirrer

SCIOLOGEX 380°C magnetic hotplate stirrers include all leading safety standards and is chemically-resistant with white ceramic work plate. They can be used in physical, chemical, analytical and biological laboratories.

Features:

- Max. heating temperature is 380°C
- High resolution LCD displays actual temperature and speed.
- Brushless DC motor is maintenance free
- Aluminum cover with ceramic work plate, allows for immediate heat transfer
- External temperature control is possible with temperature sensor PT1000
- Digital temperature control with max. temperature at 380°C
- Digital speed control with max. speed up to 1500rpm
- Max. stirring quantity of H2O at 5L



Specifications	MS-H380 Pro	MS6-Pro	HP380-Pro
Work plate Dimension	140x140mm	140x140mm	140x140mm
Work plate material	Aluminum cover with ceramic coating	Aluminum cover with ceramic coating	Aluminum cover with ceramic coating
Motor type	Brushless DC motor	Brushless DC motor	\
Motor rating input	2.4W	2.4W	\
Motor rating output	1.8W	1.8W	\
Power	510W	10W	510W
Heating output	500W	\	500W
Voltage	100-120/200-240V 50/60Hz	100-120/200-240V 50/60Hz	100-120/200-240V 50/60Hz
Stirring positions	1	1	1
Max. stirring quantity[H ₂ O]	5L	5L	\
Max. magnetic bar[length]	50mm	50mm	\
Speed range	200-1500rpm	200-1500rpm	\
Speed display	LCD	LCD	\
Temperature display	LCD	\	\
Heating temperature range	Room temp.+5°C - 380°C	\	Room temp.+5°C - 380°C
Over heat Protection	420°C	\	420°C
Temperature display accuracy	±1°C	\	±0.1°C
External temperature sensor	PT1000 (accuracy ±0.5°C)	\	PT1000 (accuracy ±0.5°C)
Control accuracy of sensor	±20rpm	±20rpm	\
Protection class	IP21	IP21	IP21
Dimension [W x D x H]	320x180x108mm	320x180x108mm	320x180x108mm
Weight	2.2kg	2.2kg	2.2kg
Permissible ambient temperature and humidity	5-40°C 80%RH	5-40°C 80%RH	5-40°C 80%RH