

# WLC 6/A2/C/2 Precision Balance



More information on the website radwag.com/en/info,w1,WP7



The drawings, photos and graphics used are for illustrative purposes only.

### **Functions**




#### Datasheet

Metrological parameters	
Maximum capacity [Max]	6 kg
Minimum load	5 g
Readability [d]	0.1 g
Verification unit [e]	1 g
Tare range	-6 kg
Repeatability	0.15 g
Linearity	±0.2 g
Stabilization time	3 s
Adjustment	internal (automatic)

Metrological parameters	
OIML Class	II
Physical parameters	
Leveling system	manual
Display	LCD (backlit)
Weighing pan dimensions	195×195 mm
Packaging dimensions	430×270×190 mm
Net weight	3.6 kg
Gross weight	4 kg
Construction	
Protection class	IP 43
Communication interface	
Communication interface	2×RS232, USB-A, USB-B
Electrical parameters	
Power supply	Adapter: 100 – 240V AC 50/60Hz 0.6A; 12V DC 1.2A Balance: 10 – 15VDC 0.6A max
Operation time on batteries	15 h (average time)
Environmental conditions	
Operating temperature	+15 ÷ +30 °C
Relative humidity	10% ÷ 85% RH no condensation

Repeatability is expressed as a standard deviation from 10 weighing cycles. Stabilization time depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.



## Accessories

Balance Storage Case Antivibration Tables Power Adapters RS 232 cables (scale - printer) Cigarette lighter receptacle power supply cables Under-pan weighing RS 232, RS 485 cables Density determination KIT


### Software

• RAD Key [WX-010-0005] • R-Lab [WX-010-0080] Displays Receipt Printer AP2-1 Current Loop Unit RS 232, RS 485 cables Protective cover for balances RS 232 cables (scale - printer) RS 232 – RS 485 Converter


RS 232 - Ethernet Converter


• Alibi Reader [WX-010-0114] • Scale Editor 2.1 [WX-010-0173]


## **Device dimensions**



WLC A1







WLC A2