



ELECTRONIC LABSCI BENCHTOP AUTOCLAVES

Designed to autoclave wrapped, unwrapped, glass and tools. Not suitable for liquids

Sterilization time up to 99 minutes

- Temperature selection from 105° to 137°C (221° to 279°F)
- Pre-loaded cycles for unwrapped instruments, wrapped/packs, glassware and additional drying cycle.
- Includes trays
- EAP Models allow closed door drying
- In-line particle filter to protect valves
- Electronic pressure and temperature sensors
- Low Water Alarm - sounds when reservoir needs to be refilled.



- Standby Heating - keeps chamber warm for quicker cycles
- Built In Printer - Provides a printed summary at the end of each cycle, documenting temperature, elapsed sterilization and drying time, selected cycle number, real time and date, as well as any errors or interruptions that may occurred during the cycle.

	LABSCI 9	LABSCI 10
Chamber Volume (L)	19	23
Max Available Height (in)	6.75"	8.3"
Chamber Dimension (in)	9" x 18"	10" x 18"
External Dimension (in)	20" x 15" x 20"	20" x 15" x 20"
Power	120V	120V
Utilities	No Plumbing Required	

	LABSCI 12	LABSCI 15
Chamber Volume (L)	34.4	65
Max Available Height (in)	10.1"	12.1"
Chamber Dimension (in)	12.2" x 18.5"	15" x 20"
External Dimension (in)	23.5" x 18" x 21.5"	26" x 21" x 27"
Power	230V, 1 phase (60 Hz NEMA 6-15) ⚡	230V, 1 phase (60 Hz NEMA 6-15) ⚡
Utilities	No Plumbing Required	

2 YEAR WARRANTY | FREE INTERNAL PRINTER