# GBK-Plus & GFK-Plus Checkweighing Scales ====ADAM











#### **Features**

- · Color-changing backlight in checkweighing mode to show if under, over or within acceptable limits
- · Large, 40mm-high easy to read digits on a bright background
- Full numeric keypad for quick and easy entering of check weighing limits
- Capacity tracker built into display for easily monitoring possible overloads
- Solid ABS housing is durable for industrial use
- Selectable language for printing
- · Rechargeable battery included for operation almost anywhere
- · Hold function freezes the displayed weight, allowing time to elapse without losing the result
- Auto power-off to save energy
- Memory accumulation totals results
- Optional USB interface simplifies data communication
- RS-232 interface provides speedy connection to computers and printers
- External calibration allows for verification and adjustment with weights
- · Selectable digital filtering for animal/dynamic weighing enables consistent results for moving subjects
- Wall-mount bracket for placing indicator on vertical surface
- 1:1,600,000 Internal counting resolution for precise results

### **Applications**

- Weighing
- Checkweighing
- · Percentage weighing
- Dynamic / animal weighing
- · Net total weighing
- · Check counting
- · Parts counting
- Accumulation

#### **About ADAM:**

For more than 50 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

# GBK-Plus & GFK-Plus Checkweighing Scales



### **Product Details**

Model	GBK-Plus 8	GBK-Plus 16	GBK-Plus 32	GBK-Plus 60	GBK-Plus 120	GFK-Plus 75H	GFK-Plus 75	GFK-Plus 150H	GFK-Plus 150	GFK-Plus 300	GFK-Plus 600	
Capacity	8kg	16kg	32kg	60kg	120kg	75kg		150kg		300kg	600kg	
Readability	0.1g	0.5g	1g	2g	5g	1g	5g	2g	0.01kg	0.02kg	0.05kg	
Weighing Units	g, kg, lb, oz, lb:oz											
Internal Counting Resolution	1:1,600,000											
Interface	RS-232, Optional USB											
Calibration	External											
Display	Backlit LCD with 40mm-high digits											
Power Supply	12VDC 800mA adapter, Internal rechargeable battery											
Operating Temperature	-10° to 40°C											
Housing		ABS Plastic indicator with die-cast aluminium base										
Overall Dimensions (DxWxH)	300 x 510 x 680mm					400 x 620 x 860mm				600 x 940 x 900mm		

#### **Accessories**

#### Item Number......Description

3052010526 ...... In-use wet cover 3074010266 ...... RS-232 cable 3074010507 ...... RS-232 to USB adaptor 1120015779..... ATP2 Thermal Printer 3126011263..... ATP2 paper 3126011281..... ATP2 paper (x10) 600002028...... AdamDU Data Collection Program

700660290...... Calibration certificate

## **Key Accessories**



#### **ATP2 Thermal Printer**

The ATP2 is a compact general purpose thermal roll printer that connects via RS-232 interface, printing results quickly and easily



#### **AdamDU Data Collection Program**

Adam DU quickly collects information from up to eight Adam balances simultaneously. An easy-to-use interface with a main command window allows the user to view and manage data capture sessions.

#### Supplied by

Adam Equipment follows a policy of continuous improvement and reserves the right to change specification and pricing without notice.

Adam Equipment's standard terms and conditions of sale apply. Errors and omissions excepted.