



ACROSS INTERNATIONAL

Model	FO19140
Electrical Requirements	208-240VAC 50/60Hz single phase, 2600 watts
Chamber Dimensions	21 x 16.5 x 22" (WxDxH)
Unit Dimensions	28 x 25.75 x 37.5" (WxDxH)
Shipping Dimensions	32 x 32 x 44" (WxDxH)
Temperature range	Ambient temperature to 250°C
Heating Elements	In the back of the oven
Timer Range	1 to 9999 minutes
Racks Included	2 (additional racks available at extra cost)
Maximum Rack Capacity	9 (height between each rack is 2 inches)
Moisture Escape Port	1.5" diameter x 2, adjustable (on top of the oven)
Access Port	2" diameter x 1, with covers
Shipping Weight	310 Lb
Certification	ETL tested to UL and CSA standards (optional), CE
Warranty	One year

Model	FO19240
Electrical Requirements	208-240VAC 50/60Hz single phase, 3200 watts
Chamber Dimensions	23 x 19 x 29.75" (WxDxH)
Unit Dimensions	30 x 28 x 46.5" (WxDxH)
Shipping Dimensions	35 x 35 x 55" (WxDxH)
Temperature range	Ambient temperature to 250°C
Heating Elements	In the back of the oven
Timer Range	1 to 9999 minutes
Racks Included	2 (additional racks available at extra cost)
Maximum Rack Capacity	13 (height between each rack is 2 inches)
Moisture Escape Port	1.5" diameter x 2, adjustable (on top of the oven)
Access Port	2" diameter x 1, with covers
Shipping Weight	440 lbs
Certification	ETL tested to UL and CSA standards (optional), CE
Warranty	One year