



## **Features**

- LCD screen shows temperature, Max. temperature up to 500°C
- 10-inch glass ceramic work plate provides excellent chemical-resistant performance and most efficient heat transfer
- External temperature control is possible by connecting the temperature sensor (PT 1000) with an accuracy at  $\pm 0.2$ °C
- The "HOT" warning will flash if the work plate temperature is above 50°C even when the hotplate is turned off
- Heating temperature: room temperature -500°C.
- Data connector: The SD card records the instrument's running data in real time.
- Timing function: the running time of the instrument can be set.

Specifications	SCI500H-Pro
Work plate Dimension [W x D]	254x254mm ( 10 inch )
Work plate material	Glass ceramic
Heating position	1
Heating temperature range	Room Temp500℃, increment 1℃
Temperature control accuracy	± 1°C (<100°C) ± 1%(>100°C)
Safety temperature	540℃
Temperature,time display	LCD
Timer function	1min-99h59min
Temperature display accuracy	±0.1℃
External temperature sensor	PT1000(±0.2℃)
"Hot" warning	50℃
Protection class	IP21
Power	1400W
Heating output	1350W
Voltage Frequency	100-120/200-240V, 50/60Hz
Dimension[WxDxH]	328x424x138mm
Weight	7.18kg
Permissibleambient temperature and humidity	5-40℃, 80%RH