

Flash Point by Automatic Abel Flash Point Tester

test method

For flash point determination of petroleum products and other liquids having flash points between -30°C and 110°C.

automatic abel flash point tester

- Conforms to IP 170 and related specifications
- Simple automation routine for easy operation
- Data Storage 200 results
- Quick Access to calibration parameters
- Auto Diagnostic
- Optional low gas cartridge to work in all types of environments
- Automatic gas cut-off at the end of the test
- Optional cryostat required for samples having a FP below 40°C
- Automatic Electronic Control of the heating rate during testing
- Heating by Solid Block Element
- Cooling by External Cryostat

The automated Abel flash point tester is used primarily to test flammable and combustible materials for shipping and safety regulations. The flash tester provides an increased temperature range of operation as compared with other testers, allowing greater flexibility in testing samples according to the Abel test method. The unit provides a test range to 110°C and can be extended to -30°C by any appropriate external chiller. The flash point tests are simply conducted by mounting the flash cup filled with sample into the test position and selecting a pre- or user-programmed test method. Automation routines provide accurate test results. A quick search method is available to determine the flash point of unknown samples. The dual detection system (thermal and ionization) allows for testing all types of products. Gas flame ignition with safety cut-off device. Electric ignition also available. Test results are automatically corrected to standard pressure (101.3 kPa). The system is equipped with a differential Pt-100 RTD probe designed to duplicate the response time of a mercury-in-glass thermometer and with multiple sensors that continually monitor instrument function, displaying an error message if a problem is detected. Supervisor software is included.

ordering information

catalog no.	description
K87390	Automatic Abel Flash Point Tester, 230V 50/60Hz

accessories

K33086	Refrigerated Circulator, 120V 60Hz (-40°C)
K33087	Refrigerated Circulator, 240V 50Hz (-40°C)
K87300-5	Flexible Stirrer Shaft and Coupling
K87300-9	Electric Ignitor
K87300-10	Tube for Propane gas 6 x 12mm (10m)



Flash Point by Automatic Abel Flash Point Tester

specifications

Conforms to the specifications of:

IP 170; ISO 13016; NF T 66-009; DIN 51755

Temperature Range:

Ambient to 110°C; Subambient to -40°C with external cooling

Electrical Requirements: 230V 50/60Hz, Single Phase

Included Accessories

SEIKO ticket printer

Abel Cup

Abel Cover

Pt 100 Probe

Detection Cable

Flexible Stirrer Shaft and Motor

Insulated Tubing for Cryostat connection

Supervisor Software

RS232C Output for connection to PC (Not Included)

General Maintenance

- Calibration Check Required at least once a year.
- Clean as frequently as possible to ensure optimum test conditions.
- Do not use Strong Solvents.
- In the case of intensive use, annual servicing is required

Dimensions l x w x h, in.(cm)

10.25x21x19.75 (26x53.5x50)

Net Weight: 44 lbs (20kg)

Shipping Information

Shipping Weight: 68 lbs (30.8kg)

Dimensions: 17x26x30



85 Corporate Drive, Holtsville, New York 11742
1-800-878-9070 (in u.s. only) TEL: +1 631 589 3800 FAX: +1 631 589 3815
Email: sales@koehlerinstrument.com www.koehlerinstrument.com

© 2025 Koehler Instrument Company, Inc.

Get it from your authorized distributor: www.labequip.com



ask@labequip.com