

SPIN AIR

Air sampler


Pharmaceutical | Food & Beverage | Environment | Cosmetics

Product Overview

Microbial air contamination monitoring is a key process in facilities with special air cleanliness needs. Spin Air samplers give users a **compact, portable, simple solution to air sampling**.

IUL's air samplers are very compact and designed for easy transportation.
Sample anywhere, anytime!

Carrying case
INCLUDED! *



*carrying case only included with Cat. N°.90005500

Main benefits

Use 100% of the Petri Dish

IUL's **Spin technology enhances air sampling and microorganisms recovery** even when sampling in mid/ highly contaminated environments (particularly useful for GMP Grade C and D cleanrooms, and regular environment sampling).

This sampling technology uses 100% of the Petri plate agar surface to plate microorganisms (only 5% is used in other air samplers), **avoiding the use of colony count correction tables**.

Full traceability

LIMS friendly data records, printer connectivity, and barcode reader compatibility. All enable full sampling traceability.

Easy cleaning

The lid can be sterilized to avoid cross-contamination.

Regulatory compliance

Spin Air sampler allows complying with USP 797 & 1116 regulations.


Easy sampling

These air samplers are compact and portable. They can be attached to a tripod for optimal sampling. If airflow problems arise, these are warned out by a noisy alarm and sampling is aborted. A handy count-down function avoids operator interference with results. Use the delayed activation mode to avoid the collector's contamination.


Available for 60 mm (Rodac) and 90 mm plates.

Spin Air technology

Competitor A




Competitor B



Competitor products have an aluminium lid design with a radial distribution of holes.

Only 5% of Petri plate is used

Spin Air IUL



Spin Air has an innovative system that stands out from the rest. With its **rotatory system**, microorganisms stay on the plate in spiral **homogeneously distributed**.

Use 100% of the Petri plate!

Duplicate simultaneous testing with the Spin Air Mate

Connect the Spin Air Mate to the Spin Air and make them run synchronously.

The Spin Air Mate enables to use two types of agars: tryptic soy agar with polysorbate and lecithin (TSApl) for bacteria and malt extract agar (MEA) for fungi isolation. Recommended by the USP chapter <797>.




Calibration

The Spin Air is calibrated at factory and ready to use! The Spin Air warns the operator when a calibration is needed. (After 2 years or for 1 million liters of sampling).

Contact IUL or your IUL's distributor, our trained professionals can help you around the world.

Sterilization


After each sampling, the lid can be sterilized with autoclave (inox and aluminium) in order to avoid any cross-contamination of the sample.



How Spin Air works

1 Preparation

Place the Petri dish and tighten the lid by screwing it on clockwise.



2 Starting

Click [] to start the process.

3 Process

The rotative system distributes homogeneously the microorganisms.



4 Results

Loosen the lid by unscrewing it in a counterclockwise direction. Petri dish is ready for incubation.

Are you ready to go a step further?

Count your plates with IUL's technology.



DOT® - Colony Counter

IUL's colony counter makes this process easier and faster through the use of LED lighting and a high quality magnifying glass.



SphereFlash® - Automatic Colony Counter

Count colonies in a simple and reliable way thanks to SphereFlash®, IUL's automatic colony counter.

Table comparision from technical data




Cat.No.90005500



Cat.No.90005532



Cat.No.90005533




Cat.No.90005502 **

MODEL	SPIN AIR	SPIN AIR BASIC	BASIC AIR
Plates	60 mm (Rodac), 90 mm	60 mm (Rodac), 90 mm	60 mm (Rodac), 90 mm
Air flow	60-100 L/min	60-100 L/min	60-100 L/min
Air volume	from 10 to 9900 l	from 10 to 9900 l	from 10 to 9900 l
Weight	1.7 kg / 3.74 lb	1.35 kg / 2.86 lb	1 kg / 2.2 lb
Dimensions (WxHxD)	15x19x21.5 cm / 5.9x7.48x8.46 in	13x15.5x23 cm / 5.11x6.1x9.05 in	13x15.5x23 cm / 5.11x6.1x9.05 in
Sampling lid dimensions (øxH)	10.5x3 cm / 4.13x1.18 in	10.5x3 cm / 4.13x1.18 in	10.5x3 cm / 4.13x1.18 in
Power	12 V	12 V	12 V
Screen	LCD	LCD	LCD
Rotation system	YES	YES	NO
Lid material (interchangeable)	aluminum	aluminum	plastic
Traceability	YES	NO	NO
Delayed activation code	YES	NO	NO
Communication	RS-232 Standard	NO	NO
Format communication	XML, CSV	NO	NO
Allows to comply with	USP-797 / USP-1116	USP-797 / USP-1116	USP-797 / USP-1116
Barcode connection	YES	NO	NO

SPIN AIR MATE
60 mm (Rodac), 90 mm
60-100 L/min
from 10 to 9900 l
1.3 kg / 2.86 lb
15x19x21.5 cm / 5.9x7.48x8.46 in
10.5x3 cm / 4.13x1.18 in
12 V
LCD
YES
aluminum
(with Spin Air)
(with Spin Air)
RS-232 Standard
XML, CSV
USP-797 / USP-1116
NO

Spin Air accessories


1



2



3



4



5



1. Set for 90 mm Petri dishes (holder and lid)
Cat. No.90005504 (aluminium)
Cat. No.90005525 (plastic)
Cat. No.90005527 (inox)

2. Set for 60 mm Rodac plates (holder and lid)
Cat. No.90005505 (aluminium)
Cat. No.90005526 (plastic)

3. Bar-code scanner
Cat. No.90005701

4. Communications Cable RS-232
Cat. No.90005510

5. Tripod with base
Cat. No.90005511
Cat. No.900011099 (base)

6. Carrying case (included with Spin Air)
Cat. No.90005534

*carrying case only included with Spin Air model

**Spin Air Mate must be connected to Spin Air Master to operate



AENOR

GESTIÓN DE LA CALIDAD

ISO 9001

For more information about Spin Air, scan the QR code

For More Information, Please Contact:

Neutec Group, Inc

1 Lenox Avenue Farmingdale, NY 11735

P: (516) 870-0877 ~ F: (516) 977-3774

www.NeutecGroup.com

