

Ramsbottom Carbon Residue of Petroleum Products

test method

Determines the 'carbon residue' left after evaporation and pyrolysis of a sample oil in the Ramsbottom furnace, providing an indication of the deposit forming tendencies of fuels and guidelines for the processing of refinery products.

Ramsbottom carbon residue apparatus

- Conforms to ASTM D524 and related specifications
- Microprocessor temperature control with digital display and overtemperature cut-off

Thermostatically controlled coking furnace for five samples. Cast-iron block type furnace reaches the standard test temperature of 550°C (1022°F) rapidly and controls with ±1°C stability. Microprocessor temperature control has °C/°F switchable digital setpoint and display. Operator and equipment are protected by an overtemperature control circuit which automatically interrupts power to the unit should block temperature exceed the programmed cut-off point. Communications software (RS232, etc.), ramp-to-set and other enhanced features are available as extra cost options. Contact your Koehler representative for information. Heavily insulated stainless steel cabinet with three-layer refractory top provides excellent heat retention.



K29100 Ramsbottom Carbon Residue Apparatus

ordering information

catalog no.	description	qty
K29100	Ramsbottom Carbon Residue Apparatus, 115V 60Hz	1
K29190	Ramsbottom Carbon Residue Apparatus, 220-240V 50/60Hz	
accessories		
332-007-001	Coking Bulb Borosilicate Glass, with capillary Conforms to ASTM D524 specifications	5
362-010-001	Sample Charging Syringe	1
382-018-001	Needle, 18 gauge, 2"	1
K27320	Coking Bulb Filling Device Convenient time saving device fills up to five coking bulbs at a time. Ideal for viscous fluids that are difficult to handle at room temperature.	1
K27200	Control Bulb Stainless steel, with IC thermocouple. May be used with a thermocouple pyrometer* to verify compliance of the furnace with ASTM performance requirements.	1
K29350	Digital Thermometer, 115V/230V	

**The K29310 Digital Thermometer is suitable for this purpose.*

specifications

Conforms to the specifications of:
ASTM D524, D6074; IP 14; ISO 4262; FTM 791-5002;
NF T 60-117

Furnace Type: Cast iron block
Capacity: 5 coking bulbs
Maximum Temperature: 650°C (1200°F)
Controller Sensitivity: ±1°C (± 2°F)
Heater: 0-2400W, ceramic band heater
Electrical Requirements:
115V 60Hz, Single Phase, 10A
220-240V 50/60Hz, Single Phase, 5A

Dimensions wxdxh,in.(cm)
14.9x12.2x15.1 (38x31x39)
Net Weight: 44 lbs (20 kg)

Software compatible, inquire with Koehler Customer Service.



85 Corporate Drive, Holtsville, New York 11742
1-800-878-9070 (in u.s. only) TEL: +1 631 589 3800 FAX: +1 631 589 3815
Email: sales@koehlerinstrument.com www.koehlerinstrument.com

©2023 Koehler Instrument Company, Inc.

Get it from your authorized distributor: www.labequip.com



ask@labequip.com