

Gardner-scrub

New!

Abrasion Scrub Tester

Coated and uncoated surfaces need to be tested for resistance to abrasion caused by a brush, sponge, scouring pad, sand paper, and other means. Abrasion resistance can be tested by wet abrasion methods using scrub media or cleaning solutions. The most common applications are testing the scrub resistance of interior wall paints, floor tiles, shower stalls, and furniture surfaces. The abrasion tester can examine the washability of a coated surface for the removal of stains. Detergents and cleaning solutions can be tested and evaluated in a reproducible manner.




Gardner-scrub Abrasion Tester

The Gardner-scrub abrasion tester offers a versatile design for abrasion and washability testing applications. The instrument arm is designed to hold from 1 - 3 brush holders. A large selection of accessories is available to customize your test requirements. An intuitive touch screen operation makes it easy to change test parameters. The Gardner-scrub has a durable chain drive mechanism for long-term reliable operation.



Gardner-scrub
touchscreen display

- Reciprocating linear motion with a constant speed over the travel distance for repeatable results
- Compact design saves on counter space
- Easy to use touch screen display
- Instrument arm holds up to 3 brush or pad holders to increase output
- User selectable scrub rate from 6 - 60 cycle/minute
- Compliant with ASTM, DIN, and ISO methods with appropriate accessories
- Up to 4 kg (8.8 lbs) can be applied to the instrument arm
- Adjustable stroke length 22.9 - 27.9 cm (9 - 11 in.)
- Optional weights for custom applications



Gardner-scrub three brush configuration with Lilly Frame

Standards

ASTM	D1792, D2198, D2486, D3206, D3207, D3450, D4213, D4488, D4828
ISO	11998
DIN	53778, 13300
Canadian Government Specification	26-GP-3a
Commonwealth of Pennsylvania Specification	W-4
US Federal Specification	P-C-431a, P-D-220A, P-R-201b, P-W-155, T-1279D, TT-P-18, TT-P-22, TT-P-23a, TT-P-26a, TT-P-29B, TT-P-30, TT-P-47a, TT-P-51d, TT-P-88a, TT-P-508
FTMS	141A, 6141, 6142
US Military Specification	MIL-C-3004, MIL-C-46057, MIL-E-11237, MIL-P-13340A, MIL-P-15422B
US Navy Specification	512C20C
Rock Island Arsenal Specification	RIX-268

Abrasion

Labequip

170 Shields Court Unit 2
Markham, ON L3R 9T5
TEL: (905) 475-5880 ext. 226
FAX: (905) 475-1231

Get it from your authorized distributor: www.labequip.com

Labequip

ask@labequip.com

Gardner-scrub Accessories

Ordering Information

Cat. No.	Description
5060	Gardner-scrub, base
5061	Gardner-scrub, ASTM D2486
5062	Gardner-scrub, DIN 53778
5063	Gardner-scrub, ISO 11998

Comes complete with:

Gardner-scrub, base

Instrument, Sample pan (5041), Power supply, Manual

Gardner-scrub, ASTM D2486

Base model (5060), 1-brush holder w/mat (5074), Nylon brush (5011), Lilly frame (5038), brass shim (6979), Glass panel (6980), scrub panels (5015)

Gardner-scrub, DIN 53778

Base model (5060), 1-Brush holder w/mat (5075), Hog Brush (5010), Pump (5037), Glass plate (6980), Scrub panels (5015)

Gardner-scrub, ISO 11998

Base model (5060), 1-Pad holder (5076), Scotch brite pads (5012), Glass plate (6980), scrub panels (5015)

Note:

For two or three brush/pad operation additional accessories must be ordered separately.

Technical Specifications

Comes with	
Instrument, Sample pan (5041), Power supply, Manual	
Base model (5060), 1-brush holder w/mat (5074), Nylon brush (5011), Lilly frame (5038), brass shim (6979), Glass panel (6980), scrub panels (5015)	
Base model (5060), 1-Brush holder w/mat (5075), Hog Brush (5010), Pump (5037), Glass plate (6980), Scrub panels (5015)	
Base model (5060), 1-Pad holder (5076), Scotch brite pads (5012), Glass plate (6980), scrub panels (5015)	
Voltage	100 - 240 V, 50/60 Hz
Dimensions	48.3 x 27.9 x 19.1 cm (19 x 11 x 7.5 in.)
Weight	14.5 kg (32 lbs)
Scrub Rate	6 - 60 cycles/minute
Stroke Length	25.4 cm (10 inch) standard setting* 22.9 cm (9 inch), 27.9 cm (11 inch) optional settings*

***Note:**

Stroke length is measured from the center brush location. The stroke length measured from the brush end add 8.9 cm (3.5 inch) to the center stroke length. The optional stroke lengths must be set by instrument supplier.

Ordering Information

Cat. No.	Description
5064	Accessory Kit, ASTM D 2486
5065	Accessory Kit, ISO 11998
5066	Accessory Kit, DIN 53778
5067	Accessory Kit, ASTM D 4213
5068	Accessory Kit, ASTM D 4828
5069	Accessory Kit, ASTM D 3450
5074	Brush Holder & Mat, ASTM
5075	Brush Holder and Mat, DIN
6979	Brass Shim
5011	Nylon Brush
5010	Hog Bristle Brush, DIN
5038	Lilly Frame
5037	Pump Assembly
5012	Scotch Brite Pads (pk of 50)
5076	Pad Holder

Accessories

Information
Includes: ASTM brush holder & mat (5074), Nylon brush (5011), Lilly frame (5038), Brass shim (6979), Glass plate (6980)
Includes: Pad holder (5076), Scotch brite pads (pk of 50) (5012), Glass plate (6980)
Includes: DIN Brush holder & Mat (5075), Hog Bristle brush (5010), Pump (5037), Glass plate (6980)
Includes: Sponge Holder 450g (5072), Polyurethane sponge (5071), Scotch brite pad (5070), Lilly frame (5038), Glass plate (6980)
Includes: Sponge holder 1000g (5073), Sponge (8116), Glass plate (6980)
Includes: Sponge holder 1000g (5073), Weight 500g (5078), Sponge (8116), Glass plate (6980)
Needed for ASTM D 2486, Dimensions: 1.5 x 3.5 inches (38.1 x 88.9 mm)
Needed for DIN 53778
Needed for ASTM D 2486
Needed for ASTM D 2486
Needed for DIN 53778
Needed for ASTM D 2486; Designed for 1, 2, or 3 brush operation
Needed for DIN 53778
Needed for ISO 11998
Needed for ISO 11998



170 Shields Court Unit 2
Markham, ON L3R 9T5
TEL: (905) 475-5880 ext. 226
FAX: (905) 475-1231



Gardner-scrub

Additional Accessories

Ordering Information		Accessories
Cat. No.	Description	Information
5072	Sponge Holder, 450g	Needed for ASTM D 4213, Dimensions: 3.0 x 3.75 x 0.875 inch (76.2 x 95.3 x 22.2 mm)
5073	Sponge Holder, 1000g	Needed for ASTM D3450, D4828. Dimensions: 3 x 3.75 x 1.0 inch (76.2 x 95.3 x 25.4 mm)
5078	Weight, 500g	Fits on top of Brush holders
5079	Weight 1000g	Fits on top of Brush holders
8116	Sponge (pack of 6)	Needed for ASTM D3450, D4828; Dimensions: 3.0 x 3.75 x 1.5 inch (76.2 x 95.3 x 38.1 mm)
5077	Sponge, B (pack of 6)	Designed for Brush Holder 5074, Dimensions: 1.5 x 3.5 inch (38.1 x 88.9 mm)
5071	Sponge, Polyurethane (pack of 6)	Needed for ASTM D4213; 3.0 x 3.5 inch (76.2 x 95.3 mm)
5070	Scotch Brite Pad, ASTM	Needed for ASTM D 4213, Dimensions: 3.0 x 3.75 inch (76.2 x 95.3 mm)
6980	Glass Plate	Needed for ASTM, ISO, DIN methods
5041	Sample Pan	Replacement; Comes standard with base model
8129	Scrub Media, Abrasive 474 ml (1 pint)	Needed for ASTM D 2486
8130	Scrub Media, Non-abrasive 474 ml (1 pint)	Needed for ASTM D 3450
5015	byko-chart Black Scrub Panels P121-10N	Box of 100; Needed for ASTM, DIN, and ISO methods, Dimensions: 165 x 432 x 0.25 mm (6.56 x 17 x 0.01 in.)
5016	byko-chart White Scrub Panels, P122-10N	Box of 100; Dimensions: 165 x 432 x 0.25 mm (6.56 x 17 x 0.01 in.)
8113	Hog Bristle Brush, ANSI	Perforated back for ANSI method Z 124.1; Fits brush holder 5074
8111	Hog Bristle Brush	General use, 3.5 x 1.5 in. (8.9 x 3.8 cm); Fits brush holder 5074
8117	Sandpaper Attachment Kit	Meets method MIL-E-11237 specification; Includes Sandpaper holder, Rubber mat, 10 yards (914 cm) x 2 inch (5.1 cm) of 1/0 and 3/0 emory cloth.
5058	Sandpaper Holder	Designed to hold any flat, thin sheet or cloth-type material with a minimum sample size of 2 x 5 inch (50.8 x 127 mm). Weight: 1 lb (454 gm)
8118	Weight, for Sandpaper Holder	Weight: 3.5 lbs (1.59 kg)
2230	Dow Latex Applicator	Needed for ASTM D 2486.

Ordering Information

Part No.	Description	Additional Information
PB-8110	Brush Holder and Mat	Needed for ASTM D 2486; Holds brushes listed below; Dimensions 1.5 x 3.5 inches
PB-8111	Hog Bristle Brush	Non-perforated
PB-8112	Nylon Brush	Meets ASTM D 2486
PB-8113	Hog Bristle Brush	Perforated for ANSI method Z 124.1
PB-8115	Sponge Holder (7.6 x 9.5 cm)	Dimensions: 3 x 3.75 inches
PB-8116	Sponge	
PB-8129	Scrub Medium Abrasive, 1 pint	Needed for ASTM D 2486; Extremely uniform medium for performance of scrub tests; Simulates effect of commercial cleaning compounds; Abrasive medium contains silica for accelerating the tests.
PB-8130	Scrub Medium Non-abrasive, 1 pint	Needed for ASTM D 2486; Non-abrasive
PB-8119	Liquid Container	For containing wet solution for testing; 1200ml capacity; Comes with mounting stand
PB-8120	Lilly Frame	Needed for ASTM D 2486; For confining media to area of path of brush or sponge; Rubber gasket with adjustable width; Includes 4 "C" clamps; Length: 17.1 inches
PB-8121	Frame	Similar to Lilly Frame; Fixed path width for use with brushes only; Includes 4 "C" clamps
PB-8122	Brass Shim	Needed for ASTM D 2486; For attaching to middle of glass test plate under scrub panel; Dimensions: 6.5 in x 0.5 in x 10 mils