



170 Shields Court Unit 2
Markham, ON L3R 9T5
TEL: (905) 475-5880 ext. 226
FAX: (905) 475-1231

Tuttnauer Manual Autoclave Series

Simplicity at Work

M/MK

The Manual Autoclave is an affordable sterilizer for private clinics that do not want to compromise on quality, safety and reliability.

Tuttnauer manual autoclaves are an effortless Plug n' Play solution. After installation, the sterilizer is virtually maintenance free with reduced running costs.

Benefits:

- Tuttnauer Manual Autoclaves last longer
- Durable components significantly reduce maintenance expenses
- Ease of use eliminates the need for specialized staff to operate sterilizer

Safety and Convenience Features:

- Heat insulation and quiet operation for pleasant office environment
- Durable 316L type stainless steel chamber and door with electro-polish finish
- Double locking safety device prevents door from opening while chamber is pressurized
- Pressure activated lock prevents door from opening if chamber is pressurized
- Door failure protection prevents door from opening at high pressure
- Automatic safety shutoff prevents overheating
- Insufficient water detector with automatic shutoff



- 1 Pressure Gauge
- 2 Timer
- 3 Thermostat
- 4 Function Selector





170 Shields Court Unit 2
Markham, ON L3R 9T5
TEL: (905) 475-5880 ext. 226
FAX: (905) 475-1231

64/85 Liter Chamber Models



19/23 Liter Chamber Models

34 Liter Chamber Models



7.5 Liter Chamber Models

Complies with strict international directives and standards:

PED 97/23 • MDD 93/42 • ASME • UL/EN 61010-1 • FDA • ISO 13485:2003 • ISO 9001:2000



0344

Model	Chamber Volume	Cold Cycle Time	Hot Cycle Time
M Series			
2340M	19 Liter	20 min.	12 min.
2540M	23 Liter	22 min.	14 min.
3140M	34 Liter	25 min.	17 min.
3850M	64 Liter	29 min.	17 min.
3870M	85 Liter	31 min.	20 min.
MK Series			
1730MK (Valueclave)	7.5 Liter	12 min.	9 min.
2340MK	19 Liter	12 min.	9 min.
2540MK	23 Liter	12 min.	9 min.

Tested for unwrapped instruments. Cycle times includes heatup, sterilization exposure and exhaust . All cycle times may vary with instrument load and voltage.

