

BENCHTOP EDXRF ELEMENTAL ANALYZER



WWW.KOEHLERINSTRUMENT.COM

BOHEMIA, NEW YORK • HOUSTON, TEXAS

BENCHTOP EDXRF ELEMENTAL ANALYZER



K47910

Specifications

Conforms to the specifications of:

ASTM D4294, D5059, D6481, ISO 20847, ISO 8754, IP 496, IP 336, JIS K 2541-1

Excitation:

50 kV X-Ray Tube

4W Maximum Power

6 Tube Filter Positions with Optics

Spill/Contamination Protection

Detection:

High Performance Silicon Drift Semiconductor Detector

Peltier Thermo-Electric Cooling

High Spectral Resolution and Count Rate

Detection Limits (LLD):

Sulfur: 2 ppm in Air (1.3 ppm in He)

Nickel: 1.5 ppm

Vanadium: 0.6 ppm

Lead: 0.0003 g/L

Sample Chamber:

Large 190 x 165 x 60 mm sample chamber

Single Position 32 mm sample aperture

Single Position 40 mm sample aperture

Bulk Sample Aperture

User Interface:

8" WVGA Touch Screen Interface

Embedded Computer

Internal Thermal Printer

USB & Ethernet Connections

Environmental Conditions:

Ambient Temperatures 10 - 35°C (50 - 95°F)

Relative Humidity < 85% non-condensing

Vibration undetectable by human

Free from corrosive gas, dust, and particles

For the determination of total sulfur in petroleum and petroleum products that are single-phase. These materials can include diesel fuel, jet fuel, kerosene, other distillate oil, naphtha, residual oil, lubricating base oil, hydraulic oil, crude oil, unleaded gasoline, gasohol, and similar petroleum products.

Also, for the determination of the total lead content of a gasoline.

EDX2000 Elemental Analyzer

The K47910 EDXRF can analyze a large array of elements from 11Na to 92U in solids, liquids, alloys, powders and thin films. The Plus model features a Silicon Drift Detector which delivers exceptional short-term repeatability and long-term reproducibility with excellent element peak resolution. Also, the K47901 features a modern smartphone style "icon-driven" user interface and built-in thermal printer. Network connections enable LIMS connectivity.

Software

- Qualitative and Quantitative Analysis
- Normalization and Validation Feature
- Fundamental Parameters
- Data Export Function with LIMS compatibility
- User Selectable Shaping Times
- Simple Flow Bar Wizard to create new applications
- Icon Driven Graphical User Interface
- Password Protection

Dimensions wxdxh,in.(cm)

13 x 17 x 14.8 (33.1 x 43.2 x 37.6)

Net Weight: 35 lbs (16 kg)

Electrical Requirements

100/240V, 1.4A, 50/60Hz

Single Phase AC

Ordering Information

Catalog No.

K47910 EDX2000 Benchtop EDXRF Elemental Analyzer, 100/240V

Accessories

K47900-1 6 Position 32 mm Automatic Sample Changer

K47900-2 5 Position 40 mm Automatic Sample Changer

K47900-3 Helium Purge Option

K47900-4 2-Stage Helium Regulator



1595 SYCAMORE AVENUE • BOHEMIA, NEW YORK 11716-1796
1-800-878-9070 (IN U.S. ONLY) • TEL: +1 631 589 3800 • FAX: +1 631 589 3815
WWW.KOEHLERINSTRUMENT.COM • EMAIL: SALES@KOEHLERINSTRUMENT.COM