

Product Name:	
Description:	<p>Premier Pharmacy/Vaccine Solid Door Refrigerator 72 Cu. Ft. capacity Three swing solid doors, self-closing, right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms 2 probes; 1 in air and 1 in sample bottle Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back 18 total shelves, 12 adjustable plus 6 additional Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½") probe access port (¾") White powder-coated steel exterior and interior Hydrocarbon, natural refrigerant (R290) Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 81" W x 34" D x 81 ¾" H with casters; 78 ¼" H without casters Cycle defrost 115V, 60 Hz, 7.5 Amps, 1/2 HP ETL listed Shipping weight: 600 lbs.</p>