

9.5 x 8 in.

Technical Data: Speed Range: 50 to 300 rpm 10 rpm 19mm (3/4 in.) Orbit: 4 x 1L or 4 kg Maximum Capacity Standard Platform Dims. 9.5x8 in. / 24x20 cm 13.1x11.74x4.7 in. 33x30x12 cm Weight: 12 6s./5.5 kg Operating Temp: 4 to 65 ℃ 100 - 240V 50-60Hz Electrical:

ORBI-SHAKER™JR.

- Perfectly circular 19mm orbit for aeration and mixing
- Digital speed control up to 300 rpm
 - Available with MAGic Clamp™ Platform

The Orbi-Shaker JR. is a space-saving shaker, complete with a 9.5 x 8 in. non slip, rubber coated platform that is ideal for tissue culture flasks, petri dishes and staining trays.

Additional platforms are also available for the Orbi-Shaker JR, including the convenient MAGic Clamp™ platform (patent pending) for use with Erlenmeyer flasks and test tube racks. The unique, magnetic attachment method is the easiest way to instantly change between flask clamps of different sizes.

Ordering Information:

BT302*	Orbi-Shaker JR with non-slip, rubber mat platform (9.5 x 8 in.)
H1000-MR	MAGIc Clamp™ universal platform (9.5x11.5") for flasks & tube racks
H1000-MR-50	Clamp for Magic Clamp platform, 50ml (max. 20)
H1000-MR-125	Clamp for Magic Clamp platform, 125ml (max. 12)
H1000-MR-250	Clamp for Magic Clamp platform, 250ml (max. 8)
H1000-MR-500	Clamp for Magic Clamp platform, 500ml (max. 6)
H1000-MR-1000	Clamp for Magic Clamp platform, 1000ml (max. 4)
H1000-MR-1550	Tube rack for Magic Clamp platform, 12x50 and 21x15 ml conical tubes (max. 2)
RT300-RP	Rolling har platform for uncommon vessels

*To order an item in 230V, add (-E) to item number.

ORBI-SHAKER™

- Large platform, up to 24 x 125ml, 14 x 250ml, 9 x 500ml, 5 x 1L or 2 x 2L
- Digital speed control up to 300rpm
- [⊥] Avallable with the MAGIc Clamp™ Platform

The powerful Orbi-Shaker is capable of mixing a 14lb load capacity up to speeds as high as 300 rpm. The standard platform (included) features a non-slip, rubber coated surface, ideal for tissue culture flasks, petri dishes and staining trays.

The convenient MAGic Clamp™ platform (patent pending) is also available for use with Erlenmeyer flasks and test tube racks. The unique, magnetic attachment method is the easiest way to instantly change between flask clamps of different sizes.

Technical Data	<u>:</u>
Speed Range:	30 to 300 rpm
Speed Increment	1 rpm
Orbit:	19mm (3/4 in.)
Maximum Capacity:	2 x 2L or 6 kg
Standard Platform Dims.	13x12 in. / 33x30 cm
Dimensions (WxDxA):	11 x 17 x 3 in. 20 x 43 x 7.5 cm
Weight:	25 bs. / 11.25 kg
Operating Temp:	4 to 65°C
Electrical:	120V or 230V, 50-60Hz

Ordering Information:

Ordering in	THREE CONTRACTOR OF THE CONTRA
BT3001*	Orbi-Shaker™Orbital Shaker with non-slip rubber mat platform (13 x 12 in.)
BT3000-MR	MAGic Clamp™ universal platform (14x12") for flasks & tube racks
H1000-MR-50	Clamp for MAGic Clamp platform, 50ml (max. 30)
H1000-MR-125	Clamp for MAGic Clamp platform, 125ml (max. 24)
H1000-MR-250	Clamp for MAGic Clamp platform, 250ml (max. 14)
H1000-MR-500	Clamp for MAGic Clamp platform, 500ml (max. 9)
H1000-MR-1000	Clamp for MAGic Clamp platform, 1000ml (max. 5)
H1000-MR-2000	Clamp for MAGic Clamp platform, 2000ml (max. 2)
H1000-MR-1550	Tube rack for MAGic Clamp platform, 12x50 and 21x15 ml conical tubes (max. 2)
H1000-P-MP	Dedicatedplatform, 4x microplates (standard or deepwell)
H1000-P-SP	Spring rack platform, for uncommon vessels and containers
	*To order an item in 230V. add (-E) to item number.



ORBI-SHAKER[™] Selection Guide







Model:	Orbi-Shaker JR	Orbi-Shaker	Orbi-Shaker MP	Orbi-Blotter
Max. Speed	300 rpm	300 rpm	1500 rpm	70 rpm
Min. Speed	50 rpm	30 rpm	200 rpm	3 rpm
Orbit Size	19mm	19 mm	3 mm	19 mm
Flask Capacity (125ml)	12	24	N/A	24*
Flask Capacity (250ml)	8	14	N/A	14*
Flask Capacity (500ml)	6	9	N/A	9*
Flask Capacity (1L)	4	5	N/A	5*
Flask Capacity (2L)	N/A	2	N/A	3*
Microplate Capacity	N/A	4	4	N/A
Control	Digital	Digital	Digital	Analog

*For low speed applications (not requiring clamps) only.

Also Available from **Benchmark**





- Exceptional temperature uniformity
- + Extremely compact, just 11" wide
- Exchange flask clamps in one second with the new MAGic Clamp magnetic system





- Designed for use in CO2 Incubators and other extreme environments
- Remote control, adjust settings without exposing
- # Exchange flask clamps in one second with MAGic Clamp™ platform.

