

3870M Large Capacity Sterilizer

TuttnauerTM
Your Sterilization & Infection Control Partners



3870M

Item No.	Chamber Dimensions Ø x L in(mm)	Volume	Overall Dimensions DxWxH in(mm)	Standard Cassettes	Tray Dimensions DxWxH in(mm)	No. of Trays	Standard Unwrapped Cycle Time	Voltage(V) Freq.(Hz)	Power(W) Current(A)	Shipping Weight lbs(kg)
3870M with stand	15"x30" (384x760)	22gal/85L	34.5"x26"x20.6" (875x665x525)	15 Full	26.6"x11.3"x1" (675x286x25) 26.6"x13.8"x1" (675x350x25)	2	Cold: 32 mins Hot: 23 mins	230V 50/60	3000W 13.6A	209 (95)

Features

- Automatic shut off at the end of both the sterilization and dry cycles
- A long life electro polished chamber and door
- Double safety locking device prevents door from opening while chamber is pressurized
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir
- Dual safety thermostat to protect against overheating
- Supplied with a 3 shelf stand
- 1 year parts and labor warranty

Control Panel



Tuttnauer USA Co. Ltd., 25 Power Drive, Hauppauge, NY 11788
Tel: (800) 624 5836, (631) 737 4850, Fax: (631) 737 0720
Email: info@tuttnauerUSA.com, www.tuttnauerUSA.com

TuttnauerTM
Your Sterilization & Infection Control Partners